Serial N .: 09/606,369 **Filed**: June 28, 2000

Pending Claims

13. A hybridization chamber comprising:

a) a base plate wherein a base cavity for holding a first array component is formed in said

base plate;

b) a lid comprising at least one component port for immobilizing a second array

component;

c) a sealant between said base plate and said lid.

14. The chamber according to claim 13, wherein said second array component is a fiber optic

bundle.

15. (Amended) The chamber according to claim 13 further comprising at least one alignment

feature, wherein said at least one alignment feature facilitates alignment of said lid with said base

plate.

16. (Amended) The chamber according to claim 13 further comprising at least one alignment

feature, wherein said at least one alignment feature is a male and female fitting.

17. (Amended) The chamber according to claim 13, wherein said first array component is a

microtiter plate.

18. (Amended) The chamber according to claim 13, wherein said chamber is connected to at least

one fluid handling device.

29. A hybridization chamber comprising:

a) a base plate comprising a base cavity;

b) a first array component in said base cavity;

b) a lid comprising at least a first component port, wherein said component port

comprises a second array component;

Serial No.: 09/606,369 **Filed:** June 28, 2000

c) a sealant between said base plate and said lid.

30. (Amended) The chamber according to claim 29, wherein said first array component is a microtiter plate.

- 31. (Amended) The chamber according to claim 29, wherein said second array component is a fiber optic bunch.
- 32. (Amended) The chamber according to claim 29 further comprising at least one alignment feature wherein, said at least one alignment feature facilitates alignment of said lid with said base plate.
- 33. The chamber according to claim 29, wherein said at least one alignment feature is a male and female fitting.
- 34. (Amended) The chamber according to claim 29, wherein said chamber is connected to at least one fluid handling device.